

TECHNICAL DATA SHEET

Stanilite®

Platinum exit LED evago wall mount



Range

Platinum range

Product group

Exit LED evago



Features







- Low power consumption and LED light source for reduced operation and maintenance costs
- Advanced charging technology combined with Lithium iron phosphate battery for long life and low maintenance



- Bright and uniform exit face luminance
- Architecturally pleasing frameless slim line design
- First-fix plate for quick and easy installation and maintenance
- 24m viewing distance
- Product comes standard with running man pictograph straight. Other pictograph diffuser options (arrow left/right) can be ordered separately - see accessories





| Dimensions | | | | |
|--------------|----------------------|------------------|-------|--------|
| | Item | Length | Width | Height |
| | Control module | 159mm | 52mm | 41mm |
| | Diffuser assembly | 335mm | 12mm | 184mm |
| Weight | | | | |
| | Model | Weight | | |
| | EM | 1.6kg | | |
| Construction | | | | |
| | Part | Construction | | |
| | Body | Diecast aluminum | | |
| | Light guide | Polycarbonate | | |
| | Diffuser | Acrylic | | |

| Light source | 1 | | | |
|-------------------|-------|-------------------|---------------------------|--|
| | Model | Light source | | |
| | EM | Multiple LED 0.6W | | |
| Power consumption | | | | |
| | Model | Power consumption | | |
| | EM | 2.0W average | | |
| | | | Note: Preliminary results | |

Note:

⁻ Designed to comply with AS2293 and meet relevant Australian EMC standards